

HD39HDR



- 4K Signal Compatible
- HDR Compatible
- Bright 4,000 ANSI Lumens
- Powerful 10W Speaker
- 15,000 Hours Long Lamp Life
- Full 1080p 3D
- 26 dB Quiet Operation

Specification

Resolution	1080p (1,920 x 1,080)	Speaker (W)	10W Speaker
Brightness ¹	4,000 ANSI lumens	3D	Yes
Contrast	50,000:1	Standby power	<=0.5W
Lamp life (hours)	15,000/10,000/4,000 (Eco+ Mode/Eco Mode/Bright Mode)	Light Source	Lamp
Noise level (Eco mode)	26dB	Scan Rate	Horizontal : 15.375~91.146 KHz Vertical : 50~85Hz
Display Colors	1.07 billion	Power supply	100V ~ 240V ± 10%, 50-60Hz
Dimensions / Weight	316x243.5x98mm(w/o feet) ; 3kg	Power Consumption	Typical 230W MAX 253W @ 110VAC (Bright)
Throw ratio	1.124~1.467		Typical 225W MAX 248W @ 220VAC (Bright)
Zoom type	1.3x		Typical 190W MAX 209W @ 110VAC (Eco)
Image size (inch)	40.2"~300"		Typical 187W MAX 206W @ 220VAC (Eco)
Aspect ratio	Native 16:9		
Keystone correction	+/-40 degree (Vertical)	Features	4K Signal Compatible
Projection Lens	F: 2.43(Wide)~2.67(Tele) f : 21.86mm(Wide)~24.00mm(Tele)		Bright 4,000 ANSI Lumens
Offset	116%±5%		Powerful 10W Speaker
Connections	HDMI 2.0x1 (HDCP 2.2 supported) HDMI 1.4x1 (HDCP 2.2 supported) USB-A 2.0x1 VGA-INx1, VGA-OUTx1 Audio-INx1, Audio-OUTx1, RS232x1		Full 1080p 3D 26 dB Quiet Operation